

CODE: MBK21-INIM-ID200

ERP: 0141213

Heat detector Detectors

Heat detector



CHARACTERISTICS

Operating voltage	10-30 Vdc
Consumption during standby	70 uA
Consumption during alarm	Max 40 mA
Sensitivity	A1R (58°C + RoR) – B (72°C) – BR(72°C + RoR) – A2S (58°C)
Operating temperature	-5°C + 40°C °C
Height including base	54mm
Diameter	110mm
Weight (with base)	160g
Weight (without base)	90g

Issue Date: 07/07/2023

Information may change

HEADQUARTERS: KATHIANA AKROTIRIOU P.C. 73100 CHANIA, CRETE - GREECE, TEL.: +30 28210 63222, FAX :+30 28210 91644

ATHENS DISTRIBUTION CENTER: SHINEZA - ASPROPIRGOS, P.C. 19300, ATTICA - GREECE, TEL.: +30 210 4614006, FAX: +30 210 5595986

NORTH GREECE DISTRIBUTION CENTER: 8 ARKADIOU str. KALOCHORI - THESSALONIKI, P.C. 57009, TEL.: +30 2310 785668, FAX: +30 2310 574793

CENTRAL & EAST CRETE DISTRIBUTION CENTER: P' str. INDUSTRIAL ZONE OF HERAKLION - CRETE - GREECE, P.C. 71601, TEL/ FAX: +30 2810 333151

www.mobiakfire.com